

Agromayal Botanica, S.A. de C.V.
Calle Guanacevi 245 Parque Industrial Gómez Palacio.
Gómez Palacio, Durango CP 35078
Tel. 52-871-750-0846
e-mail: info@amb-wellness.com
Web Page: www.amb-wellness.com

TECHNICAL DATA SHEET

ALOE HIGHPOL 30/35 IASC

INCI NAME: ALOE BARBADENSIS LEAF JUICE POWDER

CAS NUMBER: 85507-69-3
PRODUCT CODE: 1065

Specification	Analitic Method
FINE HOMOGENEOUS POWDER	VISUAL
99% THROUGH NO. 100 MESH	CPA-024
OFF WHITE TO LIGHT BEIGE	VISUAL
TYPICAL OF ALOE	ORGANOLEPTIC
TYPICAL OF ALOE	ORGANOLEPTIC
Specification	Analitic Method
NMT 8%	CPA-003
NMT 35%	CPA-008
3.5 - 5.0	CPA-002
1.002 - 1.020	CPA-022
1-2	COLORIMETER
30 - 35%	GPC
NMT 0.1 PPM	UPLC UV
Specification	Analitic Method
NMT 500 CFU/G	BAM-FDA: CH. 3
NMT 100 CFU/G	BAM-FDA: CH. 18
NEGATIVE	BAM-FDA: CH. 4
Specification	Analitic Method
NONE	NMR
	FINE HOMOGENEOUS POWDER 99% THROUGH NO. 100 MESH OFF WHITE TO LIGHT BEIGE TYPICAL OF ALOE TYPICAL OF ALOE Specification NMT 8% NMT 35% 3.5 - 5.0 1.002 - 1.020 1-2 30 - 35% NMT 0.1 PPM Specification NMT 500 CFU/G NMT 100 CFU/G NEGATIVE Specification

^{*}RECONSTITUTED TO 0.5% TOTAL SOLIDS SOLUTION.



Agromayal Botanica, S.A. de C.V.
Calle Guanacevi 245 Parque Industrial Gómez Palacio.
Gómez Palacio, Durango CP 35078
Tel. 52-871-750-0846
e-mail: info@amb-wellness.com
Web Page: www.amb-wellness.com

TECHNICAL DATA SHEET

ALOE HIGHPOL 30/35 IASC

INCI NAME: ALOE BARBADENSIS LEAF JUICE POWDER

CAS NUMBER: 85507-69-3 PRODUCT CODE: 1065

SHELF LIFE:

24 months after date of production in an unopened container, in a fresh and dry place, without exposure to sunlight. Incorrect handling of material could cause contamination of the product. After the packaging of the product is opened, shelf life is not

PACKAGING:

Standard packaging: 25kg, double polyethylene bags inside a fiber drum. Other packaging: 1kg, 2kg, 5kg and 10kg; we can also customize the packaging size that better fits your production needs.

STORAGE AND HANDLING CONDITIONS:

Product is highly hygroscopic; it must be stored in a dry place. Special measures must be taken for countries with a relative humidity level above 45% to avoid caking. The use of desiccant material is recommended.

A recommendation about stacking: the maximum stacking level is of 4 drums, if you pile more than 4 drums it will cause the bottom fiber drum to crack.

Unused portions should be kept in an airtight container, and should not be exposed to a moist environment. Wrong handling of our packaging can result into the damage of the quality of the product. Product damage because of forklift

Wrong handling of our packaging can result into the damage of the quality of the product. Product damage because of forklift hits can produce leaks.

